

PH10MQ motorised probe head

SALES & SERVICE:
A Tech Authority, Inc.
13745 Stockton Ave.
Chino CA 91710
909-614-4522
sales@atechauthority.com


Increase throughput and CMM working volume with a PH10MQ

The PH10MQ is a quill version of the PH10M motorised probe head. It is designed to increase throughput by giving DCC machines the capability of probe re-orientation while maximising the CMM working volume. The probe is able to inspect features at different angles without the need for frequent, time-consuming, stylus cluster changes.

PH10MQ is compatible with a range of both contact and non-contact scanning sensors and touch trigger probes, allowing the size, position and form of critical features to be determined.

Renishaw's autochange systems, used in conjunction with PH10MQ, provide fast repeatable probe and extension bar exchange, without the need for re-qualification of the stylus tip, helping to maximise productivity.

The PH10MQ is an increasingly popular product that provides a cost effective automated probing solution for a wide range of applications.



Key benefits

Increased throughput

The ability of the PH10MQ to index automatically reduces the number of stylus changes required, thereby increasing the throughput of your CMM. Indexing is faster than stylus changing.

Improved accuracy

The PH10MQ can achieve 0.5 µm repeatability at 62 mm radius, providing accurate positioning even when using long extensions.

Increased reach and flexibility

Extension bars up to 300 mm long together with the full range of Renishaw autojoint and M8 probes can be used with PH10MQ.

Innovations

Repeatable kinematic location

The PH10MQ uses six point kinematic location for each of its 720 positions making its locking mechanism extremely repeatable.

The Renishaw autojoint


This patented feature allows repeatable automatic probe exchange without the need for stylus re-qualification.

UCC compatibility

The PH10MQ can be used in conjunction with Renishaw's UCC controller family providing a comprehensive solution.


Specification

Weight	730 g (25.7 oz)
CMM mounting	Direct to quill
Probe mounting	Renishaw autojoint (multiwired) M8 threaded probes can be used with PH10MQ via a PAA probe adaptor
Suitable controller	PHC10-2 (RS232 and IEEE versions available) or, PHC10/50 UCC daughter card
Repeatability of position	0.5 µm (0.00002 in) specified at a distance of 62 mm (2.44 in)
Cycle time	
75° move:	2.5 seconds
90° move:	3.5 seconds
Total angular movement	
A axis	0° to 105° in 7.5 steps
B axis	0° to ±180° in 7.5 steps
Total number of positions	720
Maximum drive output torque	0.45 Nm
Maximum extension bar	300 mm (11.8 in) using PAA3 probe adaptor
Temperature range	
Operating:	10 °C to 40 °C (50 °F to 104 °F)
Storage:	-10 °C to 70 °C (14 °F to 158 °F)
Hand control unit	HCU1
Autochange systems	ACR1/ACR3



Additional information

Other variants of the PH10MQ are also available. These are PH10M and PH10T, both shank mounted products. For further details on these, and related products refer to www.renishaw.com/PH10.



For worldwide contact details, please visit our main website at www.renishaw.com/contact